

## Sender Box

### TS852D

V1.1

Jan 2018

#### 1. Function



- 1) One DVI video signal input;
- 2) One Audio signal input;
- 3) Sending card is set by USB; can be cascaded to drive a larger screen, up to 4 cards cascaded;
- 4) Support adjusting brightness manually; three scales can be set: 16-grade, 32-grade and 64-grade;

Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968

- 5) Independent power supply;
- 6) Support 60Hz and 30Hz output mode;

## 2.Capability

| 60Hz mode (using two ports)                        | 30Hz mode (using two ports) |
|--|-----------------------------|
| 2048 × 640   | 4032 × 512                  |
| 1920 × 672   | 3840 × 544                  |
| 1792 × 720   | 3584 × 576                  |
| 1600 × 800   | 3392 × 608                  |
| 1472 × 880   | 3200 × 640                  |
| 1344 × 960   | 3072 × 672                  |
| 1280 × 1024  | 2880 × 704                  |
| 1024 × 1280 (require supporting by graphics card)  | 2560 × 800                  |
| 832 × 1280 ( require supporting by graphics card ) | 2368 × 864                  |
| 640 × 1280 ( require supporting by graphics card ) | 2048 × 1024                 |

Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968

### 3. Specification

| Specifications                           |                |
|--|----------------|
| Model                                    | TS852D         |
| Setting interface                        | USB            |
| Input                                    | DVI            |
| Output                                   | RJ45           |
| Net weight ( contains one sending card ) | 1.4KG          |
| Length                                   | 280mm          |
| Width                                    | 178mm          |
| Height                                   | 50mm           |
| Input voltage                            | 100 ~ 240 V AC |

**END**

Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968